



Select 8

Copeland[™]
brand products



EMERSON[™]

GACO SARL

28, Rue Bencharif Madani

25000 BELLEVUE/CONSTANTINE - ALGERIE

Tel : 031 92 54 56 / 031 93 22 23 - Fax : 031 92 13 45

Email : gacosarl@gmail.com / benkobbi_fares@yahoo.fr



Project Report

Refrigerant R404A Dew Point

High Side Properties:

Condensing Temperature °C	52.00
Condensing Abs. Pressure bar a	24.05
Dew Point °C	52.00
Bubble Point °C	51.71
Saturated vapour enthalpy kJ/kg	381.49
Specific volume of saturated vapour cu.dm/kg	6.84
Liquid Temperature °C	51.71
Liquid enthalpy kJ/kg	280.53

Low Side Properties:

Evaporating Temperature °C	-10.00
Evaporating Abs. Pressure bar a	4.34
Dew Point °C	-10.00
Bubble Point °C	-10.59
With vapour at °C	0.00
Specific volume cu.dm/kg	47.99
Enthalpy kJ/kg	369.46

Operating Conditions:

Evaporating Temperature °C	-10.00
Condensing Temperature °C	52.00
Suction Superheat K	10.00
Subcooling K	0.00

Compressor Selected D6SJ-400X

GACO SARL

28, Rue Bencharif Madani

25000 BELLEVUE/CONSTANTINE - ALGERIE

Tel. : 031 92 54 56 / 031 93 22 23 - Fax : 031 92 13 45

Email : gacosarl@gmail.com / benkobbi_fares@yahoo.fr

**PERFORMANCE AT SPECIFIED OPERATING POINT
D6SJ-400X Data at 50Hz**

Cooling Capacity kW	48.30
Power kW	30.10
COP	1.60
Current at 400V, A	52.95
Mass Flow g/s	543.00
Heat Rejection kW	76.90
Isentropic Eff. %	64.78

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	6
Displacement @ 50 Hz, cu.m/h	127
Bore/Stroke, mm	74.7/55.6
Length/Width, mm	760/565
Height, mm	545
Net Weight, kg	252
Gross Weight, kg	268
Rotalock Discharge, inch	1 3/8
Suction, inch	2 1/8
Oil Quantity, l	6.8
Frequency Range, Hz	25 - 60
Base mounting (hole dia), mm	381 x 305 (18.0)
Sound Pressure @ 1m (MT), dBA	75
Sound Pressure @ 1m (HT), dBA	74
Sound Power (MT), dBA	86
Sound Power (HT), dBA	85
High Side PS, bar(g)	32.5
Low Side PS, bar(g)	22.5

COMPRESSOR ELECTRICAL DATA (380/420V - 3~ - 50Hz)

Maximum Operating Current, A	71.8
Locked Rotor Current, A	304
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4
Deep Oil Sump	Mounted

GACO SARL

28, Rue Bencharif Madani

25000 BELLEVUE/CONSTANTINE - ALGERIE

Tel. : 031 92 54 56 / 031 93 22 23 - Fax : 031 92 13 45

Email : gacosarl@gmail.com / benkobbi_fares@yahoo.fr

***ACCESSORIES OPTIONAL***

Additional Cooling	70W Vertical Air Flow Fan
Capacity Control	Capacity Steps 66/33%
Crankcase Heater	200W Internal
Discharge Temperature Protection	Head PTC sensor
Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Unloaded start	Available
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation
Oil Control System	ALCO Trax-Oil OM3
Inverter	Emerson Industrial Automation, Unidrive M400 07 400 770

D6SJ

